

D-Link offers a full range of ST adapters which are comprised of metal outer body and inner assembly fitted with a precision alignment mechanism. The ST adapters set the standard for optical fiber interconnects. These come with a D-Hole profile and retaining nut, which prevents accidental disconnection. The combination of a zirconia alignment sleeves and precision metal housing provides consistent long-term mechanical and good optical performance.



FEATURES

- Compact design
- Telcordia, TIA/EIA, IEC compliance
- High precision alignment
- Low insertion and return loss
- Threaded with nuts or snap-in coupling
- Body zinc alloy for long life

APPLICATIONS

- Telecommunication networks
- LAN
- Data communications
- Optical equipments
- Fiber-To-The-Home
- Premises distribution

SPECIFICATIONS

Insertion Loss	≤ 0.20dB for Zirconia Sleeve
Sleeve/Ferrule Withdrawal Force	2.0N ~ 5.9N

ORDERING INFORMATION:

Single mode		Multi mode	
Product Code	Description	Product Code	Description
NAD-FSSSTST	ADAPTOR ST SM	NAD-FMSSTST	ADAPTOR ST MM

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)