

At D-Link, we adopt high precision equipments in fiber connectors product line providing the highest levels of reliability and performance. Each connector has a 2.5mm ceramic ferrule which is housed in a nickel plated brass housing. Available in both Single and Multi mode, connectors come with a 900µm and 3mm strain relief boot. Good for use with pigtail and buffered fiber cables.

FEATURES

- High Precision Ceramic Ferrule
- High Precision Nickel Plated Brass housing
- Come with a 900µm and 3mm strain relief boot



SPECIFICATIONS

Measure	ST Connector
Insertion Loss dB (Single and Multi Mode)	< 0.3
Return Loss	> 50dB UPC Style Ferrule
Pigtail Boot	900µm black (MM) yellow (SM)
Cable Boot	3mm black, 2mm upon request
Mating Cycle	Up to 1000 times
Ferrule Diameter	2.5mm ± 0.001
Ferrule Tolerance Single Mode	126 ± 0.5µm internal
Ferrule Tolerance Multi Mode	127 ± 0.5µm internal
Finish	Pre-radiused PC end, radius 10 to 25mm
Operating Temperature	- 40°C to + 85°C
Meet Standard	IEC61754-20 Optical Fiber Connector Interface
Durability	IEC61300-2-2 Fiber Optic Interconnecting Devices
Performance	IEC61753-1 Optical Fiber interconnecting devices and passive components performance standard

ORDERING INFORMATION:

NCO-FMSST09	Connector MM ST Style
NCO-FSSST09	Connector SM ST Style

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)