

## DVR-F1108-4M

4 MP/1 SATA HYBRID DVR




## KEY FEATURES

- 1 SATA (Maximum support 6TB)
- Support AHD/TVI/CVI/1080P/4MP
- Support VGA, CVBS, HDMI 1080P HD Output
- Video Compression H.264 High Profile
- 4Ch Audio Input/1 Ch Audio Output

# DVR-F1108-4M

## 4 MP/1 SATA HYBRID DVR

### DIMENSION



### INTERFACE



### SPECIFICATION

#### VIDEO

Video Compression	H.264 High Profile
Encode Ability	8ch*4MP@8fps/3MP@10fps(AHD), 8ch*1080P@15fps(5 IN 1)
Decode Ability	8ch*4MP@8fps/3MP@10fps(AHD), 8ch*1080P@15fps(5 IN 1)
Preview Ability	8ch*4MP@15fps(AHD) /8ch*3MP@18fps(AHD) / 8ch*1080P(5 IN 1)
Video Input	Pure Analog: 8ch*4MP@8fps/3MP@10fps(AHD) / 8ch*1080P@15fps/720p(5 IN 1); Mixed Input:8ch*4MP(Analog + IP), Pure Network:8ch*1080P/960P/3MP/4MP;

#### AUDIO

Audio Compression	G711A
Two Way Audio	Support

#### RECORD AND PLAYBACK

Hard Drive	1 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	8ch(pure local input mode)

#### STORAGE AND BACKUP

Space Occupation	960H:12~20G/ day*channel
	720P:10~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio:691.2M/ day*channel
Backup Mode	USB HDD

#### INTERFACE

Video Input	8ch BNC (AHD/TVI/CVI/CVBS)
Video Output	1ch VGA,1ch HDMI,1ch CVBS
Audio Input	4ch RCA
Audio Output	1ch RCA
Alarm Input	N/A
Alarm Output	N/A
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB

#### GENERAL

Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L) x 255mm(W) x 45mm(H)