

## DVR- F1216

16CH/2 SATA DVR




## KEY FEATURES

- 2 SATA (Each maximum support 6TB)
- Support AHD/TVI 720P/1080P
- Support VGA, HDMI 1080N HD output
- Video Compression H.264 High Profile
- 6Ch Audio Input/ 1 Ch Audio Output
- 4Ch Alarm Input / 1 Ch Alarm Output

# DVR- F1216 16CH/2 SATA DVR

## DIMENSION



## INTERFACE



## SPECIFICATION

### VIDEO

Video Compression	H.264 High Profile
Encode Ability	16ch*1080N@15fps
Decode Ability	16ch *1080N@15fps
Video Input (Pure Analog)	16ch*720P Support 16ch*1080P
Mixed	8ch*AHD(720P)+8ch*TVI(720P) 8ch*AHD(1080P)+8ch*IPC(720P)
Support	8ch*AHD(1080P)+8ch*TVI(1080P) 8ch*AHD(1080P)+8ch*IPC(1080P)
Pure Network	16ch*720P Support 16ch*1080P

### AUDIO

Audio Compression	G.711A
Two Way Audio	Support

### RECORD AND PLAYBACK

Hard Drive	2 SATA (Each maximum support 6T )
Record	Manual/Event/Timer
Playback	16ch(pure local input mode)

### STORAGE & BACK UP

Space Occupation	960H:12~20G/ day*channel 720P:~20G/ day*channel 1080P 20~30G/ day*channel Audio:691.2M/ day*channel
Backup Mode	USB HDD

### INTERFACE

Video Input	16ch BNC (AHD/TVI/CVBS)
Video Output	1ch VGA,1ch HDMI
Audio Input	6ch RCA
Audio Output	1ch RCA
Alarm Input	4 ch
Alarm Output	1 ch
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB

### GENERAL

Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F )
Dimension	350mm(L) x 295mm(W) x 45mm(H)