

Cat6a U/UTP Cable

PRODUCT APPLICATION

- Enhanced performance cable for transmission of high speed data, digital and analogue voice and video (RGB) signals on LANs
- Supports Gigabit Ethernet (10GbaseT) standard
- Operates at a bandwidth of 500MHz


This cable complies to the requirements of ANSI/TIA-568-C.2 90m permanent link



CONSTRUCTION

Conductor	: 23 AWG Solid bare Copper
Insulation	: High Density Polyethylene
Pairs	: 2 Insulated conductors twisted together
Separator	: Polyolefin
Sheath	: FR PVC - Corrugated Jacket

Cable Diameter: 6.5 ± 0.3 mm



ELECTRICAL CHARACTERISTICS

Characteristic Impedance	: 100 + 15 Ω
Mutual Capacitance	: <5.6nF/100m
Resistance Unbalance	: 5% Max
Capacitance Unbalance	: 330pF/100m
Delay Skew	: < 45nS
Conductor Resistance	: <9.381Ω/100m

COLOUR CODE

<u>PAIR NO</u>	<u>COLOUR</u>
1-2	White-Orange Stripe & Orange
3-6	White-Green Stripe & Green
4-5	White-Blue Stripe & Blue
7-8	White-Brown Stripe & Brown

Cat6a U/UTP Cable

TRANSMISSION CHARACTERISTICS

8dVc gW Uk /? : l fi	;` eWfja` >ae ? Sj zV4fi	@7JF V4fi ? [ž	D>V4fi ? [ž	BE @7JF V4fi ? [ž	35DžB V4fi ? [ž	BE 35DžB V4fi ? [ž
#	#ž+	('	#+ž	(\$	(7.8	(4.8
&	%ž	(&ž	\$#	(#ž*	' 5.8	52.8
#"	' ž	')ž*	\$#	' ' ž	&7.8	&4.8
#()	' &ž(\$"	' \$ž\$	&3.7	40.7
20).8	' 3.1	19.5	' 0.7	&1.8	%8.8
%#ž\$	+ž*	' "	#* ž	&) ž	37.9	%4.9
(\$ž	#&	& ž#	#(&\$ž)	31.9	\$8.9
#" "	#* ž	&#ž*	#&	%+ž%	27.8	24.8
\$" "	\$(ž#	% (ž+	##	%&ž%	21.8	18.8
\$' "	\$+ž	% ž%	#"	%)ž)	#9.8	#6.8
%" "	%)ž)	%&ž*	+ž\$	%#ž&	#8.3	#5.3
' "'	&žž*	\$(ž)	* ž	%)ž*	#3.8	10.8

MECHANICAL CHARACTERISTICS

Bending Radius	: < 4 x Cable Diameter at -20°C ± 1°
Pulling Force	: 11.5 Kgs
Temperature Range	
Installation	: 0° to +50°C
Operation	: -20° to +70°C

ORDERING INFORMATION

MODEL NAME	DESCRIPTION
NCB-6AUGRYR-305	Cat.6a U/UTP CABLE,305MTR,PVC Sheath