



DES-1016D

The DES-1016D switch provides 16 auto-sensing 10/100Mbps ports in a desktop box. The switch allows mix and match of Ethernet and Fast Ethernet in full- and half-duplex modes.

16-Port 10/100Mbps Switch for SOHO/Workgroup

The DES-1016D is an unmanaged 10/100Mbps switch designed to enhance workgroup performance while providing a high level of flexibility. Powerful yet easy to use, this device allows users to simply plug any port to either a 10Mbps or 100Mbps network to multiply bandwidths, boost response time and satisfy heavy load demands.

16 Auto-sensing 10/100Mbps Ports

The switch comes with 16 10/100Mbps ports, allowing a small workgroup to flexibly integrate to Ethernet and Fast Ethernet. These intelligent ports detect the network speed and auto-negotiate between 10BASE-TX and 10BASE-T, as well as between full and half-duplex.

Flow Control for Secure Transmission

All ports support flow control. This function minimizes dropped packets by sending out collision signals when the port's receiving buffer is full.

Auto-negotiation of MDI/MDIX Cross Over

All ports support auto-negotiation of MDI/MDIX cross over. This eliminates the need for cross over cables or uplink ports. Any port can simply plug to a server, a hub or a switch, using the usual straight-through twisted-pair cable.

Plug-and-Play

With 16 plug-and-play ports, the switch is a perfect choice for workgroups to upgrade performance in a client/server environment. The ports can be connected to servers in full-duplex, or hubs in half-duplex.

Direct Connection to Workstations

With low-cost connection per-port, the switch can be set up for direct connection from the PCs. This relieves data bottleneck by giving each workstation a dedicated bandwidth on the network.

Features

- 16 10/100Mbps ports
- Auto MDI/MDIX for each port
- Full/half-duplex support for each port
- Flow control for protection against data loss for each port
- Uto-learning of network configuration
- Secure store-and-forward switching scheme
- Per-port auto-correction of reverse twisted-pair polarity
- Compact desktop size

DES-1016D

Technical Specifications

10/100Mbps Unmanaged Switch

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet:
 - 10Mbps (half-duplex)
 - 20Mbps (full-duplex)
- Fast Ethernet:
 - 100Mbps (half-duplex)
 - 200Mbps (full-duplex)

Topology

Star

Network Cables

- 10BASE-T:
 - UTP Cat. 3, 4, 5 (100 m)
 - EIA/TIA-568 100-ohm STP (100 m)
- 100BASE-TX:
 - UTP Cat. 5 (100 m)
 - EIA/TIA-568B 100-ohm STP (100 m)

Number of Ports

10/100Mbps port x 16

Media Interface Exchange

Auto MDI-II/MDI-X for each port

Twisted-pair Rx Reverse Polarity

Auto-correction for each port

Diagnostic LEDs

Per device:

- Power

Per port:

- Link/Activity
- Full-duplex/Collision
- 100Mbps speed

Performance

Transmission Method

Store-and-forward

Filtering Address Table

8K entries per device

MAC Address Learning

Automatic update

Packet Filtering Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,810 pps per port (half-duplex)

Packet Forwarding Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,810 pps per port (half-duplex)

RAM Buffer

4Mbits per device

Physical & Environmental

Power Supply

100 - 240 VAC, 50/60 Hz 0.3A
Internal universal power supply

Power Consumption

6 watts (max.)

Ventilation

no DC fan required

Operating Temperature

0° - 40°C

Storage Temperature

-10° - 70°C

Humidity

5% - 90%

Dimensions

280 (W) x 180 (D) x 44 (H) mm

Weight

2.8 kg

Emission (EMI)

- FCC Class A
- CE Class A
- VCCI Class A

Safety

- CUL
- CB



Ordering Information

Ethernet/Fast Ethernet Switch

DES-1016D 16 10/100Mbps ports

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

| | | |
|----------------------|------------------------|------------------------|
| U.S.A. | TEL: 1-949-788-0805 | FAX: 1-949-753-7033 |
| Canada | TEL: 1-905-829-5033 | FAX: 1-905-829-5095 |
| Europe | TEL: 44-20-8731-5555 | FAX: 44-20-8731-5511 |
| U.K. | TEL: 44-20-8731-5555 | FAX: 44-20-8731-5511 |
| Germany | TEL: 49-61- 96779900 | FAX: 49-61-967799300 |
| France | TEL: 33-1-30238688 | FAX: 33-1-30238689 |
| Italy | TEL: 39-02-2900-0676 | FAX: 39-02-2900-1723 |
| Iberia | TEL: 34-93-4090770 | FAX: 34-93-4910795 |
| Sweden | TEL: 46-(0)8-564-61900 | FAX: 46-(0)8-564-61901 |
| Norway | TEL: 47-22-991890 | FAX: 47-22-207039 |
| Denmark | TEL: 45-43-969040 | FAX: 45-43-424347 |
| Finland | TEL: 358-9-2707-5080 | FAX: 358-9-2707-5081 |
| Singapore | TEL: 65-6774-6233 | FAX: 65-6774-6322 |
| Australia | TEL: 61-2-9417-7100 | FAX: 61-2-9417-1077 |
| Japan | TEL: 81-3-5434-9678 | FAX: 81-3-5434-9868 |
| China | TEL: 86-010-8518-2533 | FAX: 86-010-8518-2250 |
| India | TEL: 91-22-652-6696 | FAX: 91-22-652-8914 |
| Middle East | TEL: 202-2456176 | FAX: 202-2456192 |
| South America | TEL: 56-2-232-3185 | FAX: 56-2-232-0923 |
| Brasil | TEL: 55-11-3094-2910 | FAX: 55-11-3094-2921 |
| South Africa | TEL: 27(0)126652165 | FAX: 27(0)126652186 |
| Russia | TEL: 7-095-737-3389 | FAX: 7-095-737-3390 |
| Taiwan | TEL: 886-2-2910-2626 | FAX: 886-2-2910-1515 |
| D-Link Corp. | TEL: 886-2-2916-1600 | FAX: 886-2-2914-6299 |



RECYCLABLE
Rev. 03 (Aug. 2002)
Printed in Taiwan