



4-PORT USB 2.0 HUB

Connect more USB devices
to your PC or Mac

Transfer data at
up to 480Mbps¹

Works with both USB 2.0
and 1.1² devices



The D-Link® 4-Port USB 2.0 Hub (DUB-H4) provides four additional USB 2.0 ports to your PC or Mac, allowing you to connect USB devices such as digital cameras, external hard drives, flash drives, and printers. Providing data rates of up to 480Mbps¹, this 4-port hub is the ideal solution for transferring data between your computer and external USB storage devices.

SIMPLE PLUG-AND-PLAY

Designed to provide quick and easy access, the DUB-H4 is equipped with four type "A" downstream ports for connecting USB peripherals or other USB hubs. The DUB-H4 does not require any software or complicated installation process. It is a Plug-and-Play device that provides seamless connectivity to both PCs and Macs. You can simply connect the DUB-H4 to your computer and start connecting your USB devices.

BACKWARD COMPATIBLE WITH USB 1.1²


The DUB-H4 is backward compatible with USB 1.1² devices, ensuring connectivity between your computer and legacy USB devices. Diagnostic LEDs located on the front of the device provide power state and port status.

The D-Link 4-Port USB 2.0 Hub (DUB-H4) is an excellent choice for adding more USB ports to your computer for connecting your existing peripherals as well as adding the latest USB cameras and external storage devices.

WHAT THIS PRODUCT DOES

The D-Link® 4-Port USB 2.0 Hub (DUB-H4) provides four additional USB 2.0 ports to your PC or Mac, allowing you to connect USB devices such as digital cameras, external hard drives, flash drives, and printers.

YOUR NETWORK SETUP



TECHNICAL SPECIFICATIONS

STANDARDS

- + USB 2.0 / 1.1²
- + OHCI (Open Host Controller Interface)
- + EHCI (Enhanced Host Controller Interface)

PORTS

- + One Upstream USB Type "B" Receptacle
- + Four Downstream USB Type "A" Receptacle

CONNECTIVITY

- Up to 127 Devices by Cascading Multiple Hubs

WIRING TOPOLOGY

- Tiered Star

DIAGNOSTIC LEDs

- + Self-powered
- + Port Status

TEMPERATURE

- + Operating: 32° to 104°F
- + Storage: -4° to 104°F

HUMIDITY

- + Operating: 5% to 95% Non-condensing
- + Non-operating: 5% to 95% Non-condensing

COMPLIANCE

- CE, FCC Class B

DIMENSIONS

- + Item (WxDxH): 4.5" x 2.5" x 1.13"
- + Packaging (WxDxH): 6.9" x 3.25" x 11.4"

WEIGHT

- + Item: 0.17 lbs.
- + Packaging: 0.9 lbs.

WARRANTY

- 1-Year Limited³

¹ For comparison purposes only. Maximum transfer rate based on USB 2.0 specifications. Actual data throughput will vary.

² Using a USB 1.1 port will affect device performance.

³ 1-Year Limited Warranty available only in the USA and Canada.

⁴ Computers must adhere to Microsoft's recommended system requirements. Please contact Microsoft for details.

⁵ Computers must adhere to Apple's recommended system requirements. Please contact Apple for details.

©2004-2007 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Windows is a registered trademark of Microsoft Corporation in the United States and other countries. Other trademarks or registered trademarks are the property of their respective owners.

MINIMUM SYSTEM REQUIREMENTS

- Computer with:
- + Windows Vista⁴, Windows® XP SP2, or Windows® 2000 SP4
 - + Mac OS® X 10.4⁵ or Higher
 - + USB 1.1² Port

PACKAGE CONTENTS

- + 4-Port USB 2.0 Hub
- + AC Adapter
- + USB 2.0 Cable
- + Quick Installation Guide