



## Cat6A FTP Keystone Jacks

### FEATURES

- RJ45 8P 8C 180° 50u Tool Less Jack
- Terminating 4 pairs, 22-26 AWG Cable
- Universal labels color coded for T568A and T568B wiring schemes
- Fitting high density keystone panel

### SPECIFICATIONS

1. RJ45 Jack Shield: Zinc die casted with Nickel plating
2. RJ45 Jack:  
Housing: Zinc die casted with Nickel plating  
Contact Bracket: PC, UL 94V-0, Transparent color.
3. RJ45 Jack Contact:  
Material: Phosphor Bronze with Nickel Plated.  
Finish: 50 micro-inch Gold Plated on plug contact area.
4. IDC:  
Housing: PC ,UL 94V-0.  
Terminal: Phosphor Bronze with Tin Plated.
5. IDC CAP : PC,UL 94 V-0
6. PCB : FR4, UL 94V-0.

### PERFORMANCE

1. T568A & T568B wiring sticker
2. Retention strength : 7.7 kg between jack and plug
3. Operation temperature :-10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA 568 C.2)
4. Life ( Mating Cycles):  
Jack: 750 cycle min  
IDC: suitable for 22-24 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools.
5. The Cat6A transmission performance is in compliance with the ANSI/TIA/EIA 568 C.2-1 standard.
6. RoHS

Product No.	Description	Color
NKJ-6ASMET2B21	Cat6A FTP 180° Keystone Jack	Silver